



Outdoor Smart Bus Stop Sign 13.3"

Empowering a New Era of Energy Efficiency

Cholesteric LCD



Anti-reflective



16.7 million colors



No flicker



UV protection



Wide temperature operation



Zero-power standby; power is only used when turning pages.



Linux



Quick refresh



On-Demand Eco-Lighting

Outdoor Smart Bus Stop Sign Specifications

Display Specifications	
Panel types	Cholesteric LCD
Size (inch)	13.3"
Resolution (Pixel)	2200 x 1650
Active Area (mm)	270.16 (H) x 202.65 (V)
Pixel Per Inch (PPI)	207
Aspect Ratio	4:3
Display color	16.7M
Viewing Angle	178° / 178°
Reflectivity	15.5%
Color Gamut	23.0% NTSC
Surface Treatment	Anti-Glare, Anti-Reflective
System Specifications	
Operating System (OS)	Linux
CPU	Dual-core Cortex-A35
RAM	1GB DDR4
Storage space	4GB eMMC
Software	iCMS
Connection Interface	
Interface	Type-C 2.0 x 1, RJ45 IN x 1
Power supply	
Power input	Type-C 12V
Outdoor Solutions	
UV protection	UV cut
Auxiliary Light Source	Front light module
IP Protection Level	Front IP65 / Overall IP54
Impact Resistance Level	IK07
Operating environment	
Temperature	-30°C ~ 80°C
Humidity	20% ~ 85%
Storage environment	
Temperature	-30°C ~ 80°C
Humidity	20% ~ 85%
Installation & Mounting	
Mounting Holes	VESA 75x75mm, Side mounting compatibility